



 Dry

 Wet

LONG-LIFE PICK

15mm Double Bar Metal Trapezoid

Our long-life grinding trapezoid: 50% taller segments than standard, for more floor per tool.

Two tall 15 mm bar segments built for long life and consistent cutting across the full range of concrete hardness. More segment height means more diamond to wear through, and a simple bond system makes it easy to match the tool to the slab.

15 mm segments

Taller than standard 10 mm segments, so there is more diamond to wear through.

Simple bond system

Four bonds, Extra Soft to Hard, color-coded on the plate.

Consistent cut

Built to cut evenly across the full range of concrete hardness.

Fits the fleet

Five mounts: Lavina, HTC/EZchange, Redi Lock, bolt-on and ASL.

TOOL LIFE & VALUE

15,000

sq ft per set*

Tall 15 mm segments (50% taller than standard 10 mm) carry more diamond to wear through: fewer change-outs per job and a lower tooling cost per square foot.

*Approximate. Actual tool life depends on concrete hardness and condition, aggregate, machine weight and speed, water use and operator technique.

Cost per sq ft = tooling spend ÷ sq ft covered

SPEND	AT 15,000
\$100	0.67¢
\$250	1.67¢
\$500	3.33¢

WHERE IT FITS

- 1 Grind
- 2 Transition
- 3 Polish
- 4 Burnish / maintain

BEFORE First cut: open the slab or remove coatings

AFTER Next metal grit, then a transition pad (Super Hybrid copper, semi-metal or the Cera series)

MACHINES

- ☒ Planetary grinder
- ☐ Angle grinder
- ☐ Floor machine / burnisher
- ☐ Power trowel
- ☐ Terrco

SURFACES

- ☒ Concrete
- ☒ Terrazzo
- ☐ Natural stone
- ☐ Overlays & toppings

APPLICATIONS

- ☐ Coating removal
- ☒ Grinding
- ☐ Transition
- ☐ Polishing
- ☐ Maintenance

JOBSITE TIPS

- Match the bond to the slab: softer bond for hard concrete, harder bond for soft concrete.
- Run each grit until the previous scratch pattern is fully removed before stepping up.

TECHNICAL SPECIFICATIONS

Segments	2 bar, 15 mm segment height
Bonds	Extra Soft, Soft, Medium, Hard
Fits	Lavina / Edco / Onfloor · HTC / Husqvarna EZchange · Husqvarna Redi Lock · Bolt-on, 3 × M6 (Diamatic, CPS, SASE, Klindex) · ASL / Iron Horse / Warrior
Speed	Planetary 1,800–2,300 RPM · Rotary 300 RPM
Grits	18/20, 30/40, 60/80, 120/150

ORDERING INFORMATION

Grit	Lavina	EZchange	Redi Lock	ASL / Iron Horse
#18/20	LV2B15-20	EZ2B15-20	RL2B15-20	HD2B15-20
#30/40	LV2B15-30	EZ2B15-30	RL2B15-30	HD2B15-30
#60/80	LV2B15-60	EZ2B15-60	RL2B15-60	HD2B15-60
#120/150	LV2B15-120	EZ2B15-120	RL2B15-120	HD2B15-120

CONTRACTORS

Ask your distributor for sequence recommendations matched to your slab and machine.

DISTRIBUTORS

Sold through authorized distributors only. Contact us for dealer pricing, stocking programs and product photos and copy.

OEM PARTNERS

We manufacture for leading tooling brands. Ask about private-label and custom specifications.



Pro Diamond Tools
prodiamondtools.com/products/15mm-double-bar-metal-trapezoid
 (657) 210-4486 ·
sales@prodiamondtools.com
 3000 S Orange Ave, Santa Ana, CA 92707