

VELCROLESS · TERRCO · RESIN

3" Terrco Direct-Mount Typhoon Resin Pads

Copper-free Typhoon resin on a Terrco direct-mount backing: dry polishing to high gloss on concrete and light-colored terrazzo.

Our Typhoon resin pad on a velcroless direct-mount backing that locks straight into the tool holders on Terrco machines. Built heavier and denser than standard resin pads, with high diamond concentration, for dry polishing from the first resin step to high gloss. No hook-and-loop to wear out and fast, secure changeovers.

 Dry

Locks in

Fits Terrco Speed Shift® holders, no hook-and-loop.

Heavier, denser

Built heavier and denser than standard resin pads.

Copper-free

No copper to stain light-colored terrazzo or concrete.

Six grits

100 to 3000, dry.

WHERE IT FITS

- ① Grind
- ② Transition
- ③ **Polish**
- ④ Burnish / maintain

BEFORE Terrco CeraCut or CeraOcto transition

AFTER Guard, burnish or maintain

MACHINES

- ☐ Planetary grinder
- ☐ Angle grinder
- ☐ Floor machine / burnisher
- ☐ Power trowel
- ☒ Terrco

SURFACES

- ☒ Concrete
- ☒ Terrazzo
- ☐ Natural stone
- ☐ Overlays & toppings

APPLICATIONS

- ☐ Coating removal
- ☐ Grinding
- ☐ Transition
- ☒ Polishing
- ☐ Maintenance

JOBSITE TIPS

- Seat each pad fully in its Speed Shift® holder before starting.
- Run dry at 2,400–3,500 RPM (planetary) or 750–1,000 RPM (rotary).
- Go 100, 200, 400, 800, 1500, 3000 without skipping; each grit should remove the scratches of the one before.
- Densify where your specification calls for it, commonly after 100 or 200.

TECHNICAL SPECIFICATIONS

Diameter	3"
Mount	Velcroless; fits Terrco Speed Shift® holders
Speed	Planetary 2,400–3,500 RPM · Rotary 750–1,000 RPM
Bond	Resin, copper-free (non-staining)
Surfaces	Concrete and terrazzo, including light-colored terrazzo
Best for	Dry resin polishing to high gloss
Grits	100, 200, 400, 800, 1500, 3000

ORDERING INFORMATION

Grit	Part #
#100	STD-3TD-100Q
#200	STD-3TD-200Q
#400	STD-3TD-400Q
#800	STD-3TD-800Q
#1500	STD-3TD-1500Q
#3000	STD-3TD-3000Q

CONTRACTORS

Ask your distributor for sequence recommendations matched to your slab and machine.

DISTRIBUTORS

Sold through authorized distributors only. Contact us for dealer pricing, stocking programs and product photos and copy.

OEM PARTNERS

We manufacture for leading tooling brands. Ask about private-label and custom specifications.



Pro Diamond Tools
prodiamondtools.com/products/3-inch-terrco-direct-mount-pads
 (657) 210-4486 ·
sales@prodiamondtools.com
 3000 S Orange Ave, Santa Ana, CA 92707

VELCROLESS · TERRCO · CERA SERIES

3" Terrco Direct-Mount CeraCut Ceramic Pads

Copper-free CeraCut ceramic transition on a Terrco direct-mount backing, safe on light-colored terrazzo.

Our CeraCut high-concentration ceramic transition pad on a velcroless direct-mount backing for Terrco machines. Goes straight from metal-bond grinding into resin, removes metal scratches fast and can eliminate one or more metal steps. Holds up when run wet.

 Dry · preferred

 Wet

Locks in

Fits Terrco Speed Shift® holders, no hook-and-loop.

Skips metal steps

Can eliminate one or more metal steps.

Copper-free

No copper to stain light-colored terrazzo or concrete.

Wet or dry

Holds up when run wet; dry preferred.

WHERE IT FITS

- 1 Grind
- 2 Transition**
- 3 Polish
- 4 Burnish / maintain

BEFORE Metal-bond grinding

AFTER Terrco Typhoon resin

MACHINES

- ☐ Planetary grinder
- ☐ Angle grinder
- ☐ Floor machine / burnisher
- ☐ Power trowel
- ☒ Terrco

SURFACES

- ☒ Concrete
- ☒ Terrazzo
- ☐ Natural stone
- ☐ Overlays & toppings

APPLICATIONS

- ☐ Coating removal
- ☐ Grinding
- ☒ Transition
- ☐ Polishing
- ☐ Maintenance

JOBSITE TIPS

- Seat each pad fully in its Speed Shift® holder before starting.
- Run right after the last metal-bond grit at 1,800–2,400 RPM (planetary) or 300 RPM (rotary); dry preferred, wet when needed.
- Go 30 to 400 and check the floor is free of metal scratches before moving to Typhoon resin.

TECHNICAL SPECIFICATIONS

Diameter	3"
Mount	Velcroless; fits Terrco Speed Shift® holders
Speed	Planetary 1,800–2,400 RPM · Rotary 300 RPM
Bond	Ceramic, copper-free (non-staining)
Surfaces	Concrete and terrazzo, including light-colored terrazzo
Best for	Transition from metal to resin
Grits	30, 50, 100, 200, 400

ORDERING INFORMATION

Grit	Part #
#30	STD-3CC-030Q
#50	STD-3CC-050Q
#100	STD-3CC-100Q
#200	STD-3CC-200Q
#400	STD-3CC-400Q

CONTRACTORS

Ask your distributor for sequence recommendations matched to your slab and machine.

DISTRIBUTORS

Sold through authorized distributors only. Contact us for dealer pricing, stocking programs and product photos and copy.

OEM PARTNERS

We manufacture for leading tooling brands. Ask about private-label and custom specifications.



Pro Diamond Tools
prodiamondtools.com/products/3-inch-terrco-direct-mount-pads
 (657) 210-4486 ·
sales@prodiamondtools.com
 3000 S Orange Ave, Santa Ana, CA 92707

VELCROLESS · TERRCO · CERA SERIES · PREMIUM

3" Terrco Direct-Mount Ultra CeraOcto Ceramic Pads

Ultra CeraOcto, our premium copper-free 8-segment ceramic, on a Terrco direct-mount backing.

Our premium 8-segment Ultra CeraOcto ceramic on a velcroless direct-mount backing for Terrco machines. Eight wedge-shaped ceramic segments bridge metal grinding and resin polishing with the highest cut rate in the Cera series, often removing one or more polishing steps.

Dry

Wet

Locks in

Fits Terrco Speed Shift® holders, no hook-and-loop.

Highest cut rate

Eight wedge-shaped ceramic segments clear metal scratches quickly.

Copper-free

No copper to stain light-colored terrazzo or concrete.

Fewer steps

Often removes one or more polishing steps; wet or dry.

WHERE IT FITS

- 1 Grind
- 2 Transition**
- 3 Polish
- 4 Burnish / maintain

BEFORE Metal-bond grinding
AFTER Terrco Typhoon resin

MACHINES

- ☐ Planetary grinder
- ☐ Angle grinder
- ☐ Floor machine / burnisher
- ☐ Power trowel
- ☒ Terrco

SURFACES

- ☒ Concrete
- ☒ Terrazzo
- ☐ Natural stone
- ☐ Overlays & toppings

APPLICATIONS

- ☐ Coating removal
- ☐ Grinding
- ☒ Transition
- ☐ Polishing
- ☐ Maintenance

JOBSITE TIPS

- Seat each pad fully in its Speed Shift® holder before starting.
- Run right after the last metal-bond grit at 1,800–2,400 RPM (planetary) or 300 RPM (rotary), wet or dry.
- Go 30 to 400 and check the floor is free of metal scratches before moving to Typhoon resin; often one or more steps can be skipped.

TECHNICAL SPECIFICATIONS

Diameter	3"
Mount	Velcroless; fits Terrco Speed Shift® holders
Speed	Planetary 1,800–2,400 RPM · Rotary 300 RPM
Bond	Ceramic, copper-free (non-staining)
Surfaces	Concrete and terrazzo, including light-colored terrazzo
Best for	Transition from metal to resin
Grits	30, 50, 100, 200, 400

ORDERING INFORMATION

Grit	Part #
#30	STD-3CO-030Q
#50	STD-3CO-050Q
#100	STD-3CO-100Q
#200	STD-3CO-200Q
#400	STD-3CO-400Q

CONTRACTORS

Ask your distributor for sequence recommendations matched to your slab and machine.

DISTRIBUTORS

Sold through authorized distributors only. Contact us for dealer pricing, stocking programs and product photos and copy.

OEM PARTNERS

We manufacture for leading tooling brands. Ask about private-label and custom specifications.



Pro Diamond Tools
prodiamondtools.com/products/3-inch-terrco-direct-mount-pads
 (657) 210-4486 ·
sales@prodiamondtools.com
 3000 S Orange Ave, Santa Ana, CA 92707