

CERA SERIES · PERFORMANCE

3" Premium CeraCut Polishing Pad

High-concentration ceramic that goes straight from metal-bond grinding into resin.

A high diamond-concentration ceramic transition pad that goes straight from metal-bond grinding into resin. It removes metal scratches fast, leaves a uniform scratch pattern and can eliminate one or more metal steps. Built to last about 20% longer than comparable ceramic transition pads, and it holds up when run wet.



 Dry · preferred

 Wet

About 20% longer life

Than comparable ceramic transition pads.

Uniform scratch

Leaves a consistent pattern for the first resin step.

Skips metal steps

Can eliminate one or more metal steps.

Wet or dry

Holds up when run wet; dry preferred. Terrco direct-mount version available.

TOOL LIFE & VALUE

15-25k

sq ft per set*

High diamond concentration for long life, and it can eliminate one or more metal steps. Both lower the tooling and labor cost of each square foot.

*Approximate. Actual tool life depends on concrete hardness and condition, aggregate, machine weight and speed, water use and operator technique.

Cost per sq ft = tooling spend ÷ sq ft covered

SPEND	AT 15,000	AT 25,000
\$100	0.67¢	0.40¢
\$250	1.67¢	1.00¢
\$500	3.33¢	2.00¢

WHERE IT FITS

- 1 Grind
- 2 Transition**
- 3 Polish
- 4 Burnish / maintain

BEFORE Metal-bond grinding
AFTER Resin polishing

MACHINES

- ☒ Planetary grinder
- ☐ Angle grinder
- ☐ Floor machine / burnisher
- ☐ Power trowel
- ☐ Terrco

SURFACES

- ☒ Concrete
- ☐ Terrazzo
- ☐ Natural stone
- ☐ Overlays & toppings

APPLICATIONS

- ☐ Coating removal
- ☐ Grinding
- ☒ Transition
- ☐ Polishing
- ☐ Maintenance

JOBSITE TIPS

- Run straight after the last metal-bond step; check the floor is free of metal scratches before moving to resin.
- On small machines, add weight so the ceramic keeps cutting instead of glazing.

TECHNICAL SPECIFICATIONS

Diameter	3"
Bond options	Hard (soft concrete) · Soft (standard to hard concrete)
Speed	Planetary 1,800–2,400 RPM · Rotary 300 RPM
Also available	Velcroless direct-mount backing for Terrco machines
Grits	30, 50, 100, 200, 400

ORDERING INFORMATION

Grit	Soft bond	Hard bond
#30	STD-3CC-030S	STD-3CC-030H
#50	STD-3CC-050S	STD-3CC-050H
#100	STD-3CC-100S	STD-3CC-100H
#200	STD-3CC-200S	STD-3CC-200H
#400	STD-3CC-400S	STD-3CC-400H

CONTRACTORS

Ask your distributor for sequence recommendations matched to your slab and machine.

DISTRIBUTORS

Sold through authorized distributors only. Contact us for dealer pricing, stocking programs and product photos and copy.

OEM PARTNERS

We manufacture for leading tooling brands. Ask about private-label and custom specifications.



Pro Diamond Tools
prodiamondtools.com/products/3-premium-ceracut-polishing-pad
 (657) 210-4486 ·
sales@prodiamondtools.com
 3000 S Orange Ave, Santa Ana, CA 92707